

GREENMAX[®] SCREW COMPACTOR APOLO C300



Compression
Ratio:
50:1



> Screw compression technology, Lower utility consumption and higher efficiency

PHENIX CONTACT **NSK**
SIEMENS **Schneider Electric**

> Reputable & High quality components make the machine reliable and durable



> Able to deal with fish boxes that contain water.



> Speed Control device is designed to avoid EPS from melting.



> SIEMENS control system guarantees easy and simple operation.




> CE approved and comply with UL/CSA standards

> APPLICABLE MATERIAL:

POLYSTYRENE			POLYPROPYLENE
EPS	EPS CUPS / TRAYS	XPS	EPP

> DIMENSIONS



> TECHNICAL DATA

ITEM	A-C300
Total Power Consumption	31.05 kw / 41.6 hp
Crusher Power Consumption	2*4 kw / 2*5.36 hp (Or according to your request)
Blower Consumption	7.5 kw / 10.1 hp (Or according to your request)
Silo Volume	10 m ³ / 12 cubic yard (Or according to your request)
Production Capacity	300 kg per hour / 660 lbs per hour
EPS Compression Ratio	50:1
Compressed EPS Density	200-400 kg/m ³ / 337-674lbs/cubic yard
EPS Block Dimensions	380*380 (w/h) mm / 15.0*15.0 (w/h) in.
Feed Hopper Door	1530*547 (l/w) mm / 60.2*21.5 (l/w) in.
Dimensions	4940*4500*4430 (l/w/h) mm / 194.5*177.2*174.4 (l/w/h) in.
Shipping Dimensions	-
Weight	2600 kg / 5721 lbs