

### **TOTAL SOLUTION TO EPS/STYROFOAM RECYCLING**

## **GREENMAX® MELTER MARSC300**





> Three stages of temperature control manipulate output color as white as possible.



> Easy operation. No Additional adjustment required during operation. Just start and stop.



> Easy 5S, Less foam scraps blow out and scatter on the ground during operation.



> Screw melting technology enables continuous output at a ratio of 90:1. High-density ingot weights up to 25T per 40HQ container load.



> Equipped with reputable PHOENIX, SCHNEIDER, NSK components, GREENMAX ensures great safety, reliability and durability.







> GREENMAX machines are CE approved and comply with UL/CSA standards.


#### > APPLICABLE MATERIAL:


POLYSTYRENE		POLYETHYLENE		POLYPROPYLENE
EPS/ EPS DUST	EPS CUPS&TRAYS/ XPS	EPE	EPE ROLL/ EPE SHEET	EPP



# TOTAL SOLUTION TO EPS/STYROFOAM RECYCLING

### > DIMENSIONS





### > TECHNICAL DATA

ITEM	M-C300		
Motor Power	47.7kw / 64.9hp		
Crusher Power	2*4 kw / 2*5.36 hp (Or according to your request)		
Blower Power	7.5 kw / 10 hp (Or according to your request)		
Silo Volume	11.5 m³ / 15 cubic yard (Or according to your request)		
Production Capacity	300 kg per hour / 660 lbs per hour		
EPS Compression Ratio	90:1		
Compressed EPS Density	600-800 kg/m³ / 1011-1348lbs/cubic yard		
Feed Hopper Door	1530*800 (I/w) mm / 60.2*31.5 (I/w) in.		
Dimensions	3400*4850*5000(I/w/h) mm / 133.9*191*196.8(I/w/h) in.		
Shipping Dimensions	-		
Weight	3200 kg / 7041 lbs		